



			·				
GENERAL SPECIFICATIONS: Tub Size 70"x40"x22.5"							
Bathing Well:	Length: 63" top / 45" Width: 43" top / 22" b Depth at overflow: 17	ottom	40	$\begin{array}{c c} 40^{\prime\prime} \\ \hline \\ \end{array} \end{array} \left(\begin{array}{c c} \\ \hline \\ \\ \end{array} \right) \\ \hline \\ \\ \end{array} \right) \\ \hline \\ \\ \end{array} \right) \\ \hline \\ \\ \\ \\ \end{array} \right) \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ $			
Average Fill:	50 gal to account for body						
Maximum Fill:	75 gal to overflow			3"			
Electrical Requirement:	1-20 amp/115 GFCI outlet						
All LX tubs are manufactured with 0.125" 100% acrylic, the thickest in the industry: Pre-leveled and framed to make installa- tion quicker and easier. Tubs are freestanding and require no additional framing or costly installation labor. Bathtub bases are made with a solid wood base and structural foam that provides support, reduces noise, and insulates.					70" 63"(), 19.5"		
FSTP SKU K		*Please specify left or right hand drain and motor placement LHD - Left Hand Drain		22.5"	45"		
	Soaker Whirlpool Air	RHD-Right Hand Drain LHM - Left Hand Motor	Fra	ame Reinforcement legs	Solid Wood Base	Stabalizing Foam	
change without not	ght measurement is inclusiv ice. Drawing shows recomm e tub before building deck. I	nended pump location a	as well a	as approximate location	of frame reinforcement	TEBZZ	

